

5

## CUTTING UNIT FOR CUTTING CONTINUOUS CIGARETTE RODS

TECHNICAL FIELD

10 The present invention relates to a cutting unit for cutting continuous cigarette rods.

BACKGROUND ART

In the tobacco industry, cigarette manufacturing machines are used which produce and feed at least one  
15 continuous cigarette rod axially, in a generally horizontal direction, to a counter-cutting device which cuts the continuous rod into a succession of cigarette portions of given length.

The continuous rod is normally cut using a cutting  
20 head of the type described, for example, in GB-2089187, which comprises a cutting drum having a number of substantially radial blades, and rotating about an axis (normally horizontal and at any rate parallel to a plane defined by the continuous rods when dealing with more  
25 than one rod) forming, with the travelling direction of the continuous rod, an angle whose size depends on the length of the desired cigarette portions. As explained clearly in GB-1095970, the size of the angle must be

adjustable to permit changes in format, i.e. in the length of the cigarette portions, and ensure the line of interference between each blade and the continuous rod moves, during the cutting operation, at the same speed as  
5 the continuous rod, so that the cut is perfectly crosswise to the axis of the continuous rod at all times.

As described, for example, in GB-2089187, to adjust the angle, the cutting head is mounted to rotate, with respect to a support, about an adjustment axis through  
10 the counter-cutting device, perpendicular to the axis of rotation of the cutting drum, and crosswise to the travelling direction of the continuous rod, and can be locked releasably in any desired angular position about the adjustment axis.

15 In all known cutting heads, locking, releasing, and rotating the cutting head about the adjustment axis call for a series of manual operations, which mean relatively prolonged machine stoppages, as well as painstaking and, at times, relatively inaccurate adjustment.

20 DISCLOSURE OF INVENTION

It is an object of the present invention to provide a cutting unit designed to eliminate the aforementioned drawbacks in a straightforward, relatively low-cost manner.

25 According to the present invention, there is provided a cutting unit for cutting continuous cigarette rods, as claimed in Claim 1 and, preferably, in any one of the following Claims depending directly or indirectly

on Claim 1.

#### BRIEF DESCRIPTION OF THE DRAWINGS

A non-limiting embodiment of the present invention will be described by way of example with reference to the accompanying drawings, in which:

Figure 1 shows a top, three-quarter view in perspective of a preferred embodiment of the cutting unit according to the present invention;

Figure 2 shows an underside, three-quarter view in perspective of part of the Figure 1 cutting unit;

Figure 3 shows a larger-scale view, with parts removed for clarity, of a detail in Figure 2;

Figure 4 shows a partly sectioned side view of the Figure 3 detail.

#### BEST MODE FOR CARRYING OUT THE INVENTION

Number 1 in Figures 1 and 2 indicates as a whole a cutting unit for cutting cigarette portions 2 of given length from two parallel continuous cigarette rods 3 produced on a known dual-rod manufacturing machine (not shown) supporting cutting unit 1.

With reference to Figure 1, continuous rods 3 are fed simultaneously at a given speed to a counter-cutting device 4 forming part of cutting unit 1 and defined in known manner by two sleeves 5, which move back and forth in a travelling direction 6 of continuous rods 3, and have respective slits 7 lying in the same plane, crosswise to direction 6, and engaged successively by a known blade 8 of cutting unit 1.

In addition to counter-cutting device 4, cutting unit 1 also comprises a supporting body 9, which, by means of a lateral connecting plate 10, is connected integrally to a fixed frame (not shown) of the manufacturing machine (not shown), projects from said frame (not shown), and is bounded at the top by a horizontal plate 11 supporting a known cutting head 12.

With reference to Figure 1, cutting head 12 comprises a casing 13 having a base plate 14 fitted to plate 11; and a cutting drum 15 projecting laterally from casing 13, and fitted to casing 13 to rotate, anticlockwise in Figure 1, about an axis 16 by means of a shaft 17 housed inside casing 13 and driven by a main motor (not shown) of the manufacturing machine (not shown). Along its outer periphery, cutting drum 15 supports a number of cylindrical, substantially radial cores 18 (only one shown in Figure 1), which are adjustable angularly about respective axes 19, and are fitted on their respective outer ends with respective known, substantially radial blades 8.

To adjust the angle formed by axis 16 with travelling direction 6, i.e. to adjust the tilt of blades 8 with respect to sleeves 5, as a function of the format, i.e. length, of cigarette portions 2 to be produced, cutting head 12 is fitted to supporting body 9 to rotate, with respect to supporting body 9, about an adjustment axis 20 (Figure 1) through counter-cutting device 4 and perpendicular to the mating plane of base plate 14 and

plate 11, to the travelling direction 6 of continuous rods 3, and to a plane defined by continuous rods 3. For this purpose, cutting unit 1 comprises a guide device 21 for guiding cutting head 12 about adjustment axis 20; an  
5 actuating device 22 for moving cutting head 12 about adjustment axis 20 with respect to supporting body 9; a detecting device 23 for determining the instantaneous angular position of cutting head 12 about adjustment axis 20, to permit negative feedback control of actuating  
10 device 22; and a releasable locking device 24 for locking cutting head 12, with respect to supporting body 9, in any desired angular position about adjustment axis 20.

As shown in Figure 3, guide device 21 comprises a rib 25 projecting upwards from plate 11 and extending, on  
15 plate 11, along an arc coaxial with adjustment axis 20; and a slot 26 formed through base plate 14, extending along an arc coaxial with adjustment axis 20 and of the same radius as the arc of rib 25, and engaged in sliding manner by rib 25.

20 As shown in Figure 2, actuating device 22 comprises a motor reducer 27 fitted to supporting body 9, beneath plate 11, and comprising an output shaft 28, which is perpendicular to plate 11, extends in rotary manner (Figure 3) through a sleeve 29 integral with supporting  
25 body 9, and through a hole (not shown) formed through plate 11, extends inside casing 13 through an opening 30 formed through base plate 14, and is fitted, above base plate 14 and inside casing 13, with a pinion 31 which

meshes with the outer teeth of a ring gear 32 integral with casing 13 and coaxial with adjustment axis 20.

As shown more clearly in Figure 2, detecting device 23 comprises a scale 33 printed on a curved lateral surface 34, coaxial with adjustment axis 20, of base plate 14; and an optical reader 35, preferably a laser reader, positioned radially with respect to lateral surface 34, and for determining, on scale 33, the angular position, with respect to an origin, of cutting head 12 about adjustment axis 20, so as to negative-feedback-control motor reducer 27. Detecting device 23 as described above may obviously be replaced by any equivalent device, e.g. a straightforward encoder (not shown) fitted to shaft 28.

As shown in Figures 3 and 4, locking device 24 comprises two pairs of pins 36 (theoretically, even only one pin 36 is sufficient), each of which is fitted in axially sliding manner through a relative hole 37 formed through plate 11, and has an end plate 38 above plate 11. In each pair of pins 36, the portions of pins 36 projecting above plate 11 engage and slide transversely inside a T-section groove 39, which opens at one end at a lateral edge of base plate 14, and comprises (Figure 3) two end portions 40a, 40b connected to each other, and each of which is engaged by a respective pin 36 and extends along a respective arc coaxial with adjustment axis 20. Each groove 39 comprises a rectangular-section channel 41 engaged in sliding manner by end plates 38 of

relative pins 36; and a slot 42, which extends centrally along relative channel 41, is engaged in transversely sliding manner by respective top end portions of relative pins 36, and defines, beneath channel 41, two shoulders  
5 43 extending along and on opposite sides of slot 42, and between relative end plates 38 and plate 11.

Beneath plate 11, each pin 36 comprises a threaded portion 44 fitted with a ring nut 45 for preloading a pack of disk springs 46 interposed between ring nut 45  
10 and a bottom surface of plate 11 to draw end plates 38 downwards and grip relative shoulders 43 against plate 11 to normally keep cutting head 12 locked contacting supporting body 9.

An end portion of each pin 36, opposite the portion  
15 supporting relative end plate 38, projects from the bottom of relative ring nut 45 to define a tappet 47 cooperating with a cam-type release device 48, which forms part of locking device 24, is common to all of pins 36, and, when activated, opposes the locking action of  
20 disk springs 46 on relative pins 36 to allow cutting head 12 to move about adjustment axis 20 under the control of motor reducer 27.

As shown in Figure 4, release device 48 comprises, for each pin 36, a U-shaped bracket 49, which is located  
25 beneath plate 11 with its concavity facing upwards, is connected integrally to plate 11, and houses the portion of relative pin 36 projecting beneath plate 11. Brackets 49 of two pins 36 in the same pair of pins 36 support for

rotation respective opposite ends of a rod 50 extending crosswise to relative pins 36 and fitted with two cams 51, each of which cooperates with a respective tappet 47 to lift relative pin 36 and release cutting head 12 with respect to supporting body 9, when rod 50 is set to a given angular work position about its own axis 52.

As shown more clearly in Figure 3, rods 50 are rotated, about respective axes 52, between said relative angular work positions and relative angular rest positions by a linear actuator 53 (Figure 2), an output rod 54 of which extends crosswise to rods 50 and is hinged to an intermediate point of a crank 55 fitted to one of rods 50 and forming part of an articulated quadrilateral 56, a further crank 55 of which is fitted to the other rod 50 and connected to the other crank 55 by a connecting rod 57.

Operation of cutting unit 1 is clear from the foregoing description, with no further explanation required. Suffice it to say that, to change format, the new format data is sent to a central control unit 58, which (though not shown graphically in Figure 2 for the sake of simplicity) activates linear actuator 53 to release cutting head 12 with respect to supporting body 9, and then activates motor reducer 27 to rotate cutting head 12 as required about adjustment axis 20 and under negative feedback control of optical reader 35. Once the new angular position is set, central control unit 58 automatically deactivates motor reducer 27, and



reactivates linear actuator 53 to lock cutting head 12 to supporting body 9 in the new angular position about adjustment axis 20.

## CLAIMS

1) A cutting unit for cutting continuous cigarette rods fed in a given travelling direction (6), the cutting unit (1) comprising a supporting body (9); a cutting head (12) fitted to the supporting body (9) to rotate about a first axis (20), the cutting body (12) comprising a cutting drum (15), which rotates about a second axis (16) forming a given angle with said travelling direction (6), and has at least one radial blade (8); a counter-cutting device (4), which is engaged by at least one said continuous cigarette rod (3), and through which said first axis (20) extends; and locking means (24) for angularly locking the cutting head (12) in position on said supporting body (9); and being characterized in that said locking means (24) comprise automatic release means (48) for releasing the cutting head (12) with respect to the supporting body (9); actuating means (27, 31, 32) being interposed between the supporting body (9) and the cutting head (12) to rotate the cutting head (12) about said first axis (20) to vary said angle.

2) A cutting unit as claimed in Claim 1, and also comprising sensor means (23) for determining said angle and for negative-feedback-controlling said actuating means (27, 31, 32).

3) A cutting unit as claimed in Claim 2, wherein said sensor means (23) comprise a scale (33) located on said cutting head (12); and a fixed optical reader (35)

for determining said angle on said scale (33).

4) A cutting unit as claimed in Claim 3, wherein said cutting head (12) comprises a curved lateral surface (34) coaxial with said first axis (20); said curved lateral surface (34) supporting said scale (33); and said optical reader (35) facing said scale and being positioned radially with respect to said first axis (20).

5) A cutting unit as claimed in any one of Claims 1 to 4, and also comprising guide means (21) interposed between the cutting head (12) and the supporting body (9) to guide the cutting head (12) on the supporting body (9) during rotation about said first axis (20).

6) A cutting unit as claimed in Claim 5, wherein said guide means (21) comprise a rib (25), which projects upwards from said supporting body (9) and extends, on the supporting body (9), along an arc coaxial with said first axis (20); and a slot (26), which is formed on said cutting head (12), extends along an arc coaxial with said first axis (20) and of the same radius as the arc of said rib (25), and is engaged in sliding manner by said rib (25).

7) A cutting unit as claimed in any one of Claims 1 to 6, wherein said actuating means (27, 31, 32) comprise a motor reducer (27) fitted to said supporting body (9); a pinion (31) parallel to said first axis (20) and activated by said motor reducer (27); and a ring gear (32) coaxial with said first axis (20), fitted to said cutting head (12), and engaged by said pinion (31).

8) A cutting unit as claimed in any one of Claims 1 to 7, wherein said supporting body (9) and said cutting head (12) comprise a first and, respectively, a second plate (11, 14) contacting each other; said locking means  
5 (24) comprising at least one pin (36) extending in axially sliding manner through said first plate (11) and fitted in transversely sliding and axially fixed manner to said second plate (14); elastic means (46) being interposed between said pin (36) and said first plate  
10 (11) to compress and lock said first and second plate (11, 14) against each other.

9) A cutting unit as claimed in Claim 8, wherein said pin (36) has an end portion comprising an end plate (38); said second plate (14) having a curved, T-section  
15 groove (39) coaxial with said first axis (20); and said end portion engaging said groove (39) in transversely sliding manner.

10) A cutting unit as claimed in Claim 8 or 9, wherein said automatic release means (48) comprise push  
20 means (51) carried by said supporting body (9) and acting on said pin (36) to move the pin (36) axially in opposition to said elastic means (46).

11) A cutting unit as claimed in Claim 10, wherein said push means (51) are cam means acting axially on said  
25 pin (36).

12) A cutting unit as claimed in Claim 11, wherein said locking means (24) comprise two pairs of said pins (36); said automatic release means (48) comprising, for

each said pair of pins (36), a rod (50), which has a third axis (52) crosswise to the relative said pins (36), and is fitted with two cams (51), each of which cooperates with one end (47) of a respective said pin  
5 (36), and an actuating device (53, 54, 56) for rotating said rod (50) about said third axis (52).

13) A cutting unit as claimed in Claim 12, wherein said actuating device (53, 54, 56) is common to said rods (50), and comprises a linear actuator (53); and an  
10 articulated quadrilateral, in turn comprising two cranks (55), each fitted to a respective said rod (50); said linear actuator (53) having an output (54) connected to one of said cranks (55).

1 / 4





Fig.1

2 / 4







Fig. 3



4 / 4

Fig. 4



# INTERNATIONAL SEARCH REPORT

International Application No

EP2004/053000

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A24C5/28

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A24C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 089 187 A (GD SOC PER AZIONI) 23 June 1982 (1982-06-23) cited in the application the whole document	1
A	US 4 693 261 A (OKUMOTO ET AL) 15 September 1987 (1987-09-15) column 4, line 24 - column 5, line 25; figure 4	1
A	US 3 782 229 A (CRISTIANI A, IT) 1 January 1974 (1974-01-01) the whole document	1, 3
A	US 6 478 031 B1 (SMITH MICHAEL NORMAN) 12 November 2002 (2002-11-12) abstract	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

21 March 2005

Date of mailing of the international search report

30/03/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

MARZANO MONTEROSSO

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

EP2004/053000

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2089187	A	23-06-1982	IT 1148241 B	26-11-1986
			BR 8108048 A	21-09-1982
			CA 1165657 A1	17-04-1984
			CS 227338 B2	16-04-1984
			DD 201972 A5	24-08-1983
			DE 3140769 A1	12-08-1982
			FR 2495898 A1	18-06-1982
			IN 157170 A1	01-02-1986
			JP 1581609 C	11-10-1990
			JP 2006507 B	09-02-1990
			JP 57110182 A	08-07-1982
			US 4398438 A	16-08-1983
US 4693261	A	15-09-1987	JP 1054030 B	16-11-1989
			JP 1567710 C	10-07-1990
			JP 60232081 A	18-11-1985
			DE 3576043 D1	22-03-1990
			EP 0163813 A1	11-12-1985
US 3782229	A	01-01-1974	NONE	
US 6478031	B1	12-11-2002	AU 3631097 A	20-02-1998
			CN 1226141 A	18-08-1999
			EP 0921731 A1	16-06-1999
			WO 9804161 A1	05-02-1998
			JP 2000515022 T	14-11-2000